

HIGHTEC POWER BOAT 4-T SAE 15W-40

High-performance engine oil developed specifically to meet the needs of modern inboard 4-stroke diesel and petrol engines with a wide range of applications in many engines and auxiliary units.

Description

HIGHTEC POWER BOAT 4-T SAE 15W-40 is a high-performance engine oil of SAE grade 15W-40 produced using selected base oils. Its exceptionally high level of performance is achieved through the interaction of these base oils and the specially developed, advanced additives.

Application

HIGHTEC POWER BOAT 4-T SAE 15W-40 has been developed specifically to meet the requirements of 4-stroke inboard diesel and petrol engines subjected to high loads. It is characterised by very good corrosion protection for all engine parts and reliably prevents deposits. It provides improved durability in the face of typical problems associated with modern boat engines such as fuel and water entry and thus guarantees good wear protection and safe operation.

Benefits

- Wide range of applications in boat engines and other diesel and petrol-driven units
- Outstanding protection against wear and corrosion
- Improved resistance to fuel entry and water contamination
- Extremely stable to shear stress - 'Stay-in-grade'
- The favourable cold viscosity ensures rapid lubrication and low 'cold wear'
- High level of oxidation protection by means of selected base oils and special additives
- Miscible and compatible with conventional and synthetic engine oils. However, in order to exploit the full benefits of the product HIGHTEC POWER BOAT 4-T SAE 15W-40, a complete oil change is recommended.

The quality of this product is equivalent to EU regulations

- ACEA E7
- ACEA A3/B4
- API SL/CI-4
- Cummins 20071/-72/-76/-77/-78
- MAN M 3275
- MTU Type 2
- Volvo VDS-3

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.88
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	104,0
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	14,3
Viscosity index	ASTM D-7042	-	140
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	242
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-29
CCS	ASTM D-5293	cP @ °C	5800 @ -20
Total base number	DIN 51639-1	mgKOH/g	10,2

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe-oil.com).

