

## HIGHTEC TURBO HD SAE 30

Premium, mineral-based, monograde engine oil for mixed vehicle fleets.

### Description

HIGHTEC TURBO HD SAE 30 is a premium monograde engine oil of SAE grade 30. Its exceptionally wide range of applications is reflected in the interaction of selected base oils with advanced additives. It can be used in Otto and diesel engines, with or without turbocharging.

### Application

HIGHTEC TURBO HD SAE 30 is used in petrol and diesel engines in mixed vehicle fleets according to the manufacturer's specification. Its modern design makes a wide range of applications possible and ensures safe operation under all operating conditions.

### The quality of this product is equivalent to EU regulations

- ACEA E7,E5,E3,E2
- ACEA A3/B4
- API CF-2/CI-4/SL
- MIL-L-2104D
- MAN M 3275-2
- MB 228.2
- MTU Type 2
- Volvo VDS

### Additionally this product is recommended when the following filling instructions are required

- Allison C-4
- CAT TO-2
- Deutz DQC I-02
- MAN 270
- MB 228.0/235.12
- ZF TE-ML 02C, 03A

### Benefits

- First-class economy grade for multi-functional use in different brands of diesel and Otto engines
- Suitable for both passenger cars and commercial vehicles, as well as agricultural and construction machinery
- Eminently suitable for turbocharged engines
- Prevention of adhesion, lacquering and coking of cylinders, pistons, valves and turbochargers in a reliable manner
- Stable lubricating film, even with hot oil and under excessive loads, and the best wear protection
- Extremely stable to shear stress - 'Stay-in-grade'
- Low oil consumption and increased oxidation protection
- Miscible and compatible with conventional and synthetic engine oils. However, in order to exploit the full product benefits of HIGHTEC TURBO HD SAE 30, a complete oil change is recommended.

### Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.882
Corrosion effect on copper	DIN 51 811	Korr.-Grad	1b
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	90,0
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	11,6
Viscosity index	ASTM D-7042	-	123
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	246
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-29
Total base number	DIN 51639-1	mgKOH/g	10,0

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe-oil.com).

ROWE MINERALÖLWERK GMBH  
Langgewann 101, D-67547 Worms



Are you looking for the correct oil for your vehicle?  
Scan this code for the ROWE-oilfinder.