# PRODUCT INFORMATION

## HIGHTEC 2-T SCOOTER

Synthetic, high-performance engine oil for air-cooled/water-cooled 2-stroke engines. Eminently suitable for mixed and separated lubrication systems.

### Description

HIGHTEC 2-T SCOOTER is a 2-stroke, high-performance engine oil produced using selected mineral and synthetic base oils. It contains a low-ash additive composition and combusts, leaving almost no residues behind. This prevents spark plug fouling and deposits in critical areas such as piston rings and outlet ports, and thus ensures a long service life of the engine.

### Application

HIGHTEC 2-T SCOOTER can be used for multi-functional purposes in air-cooled and water-cooled 2-stroke engines. It is suitable for both separate and mixed lubrication. During mixed lubrication, the mixing ratio must be observed in accordance with the engine manufacturer's specifications.

### The quality of this product is equivalent to EU regulations

- API TC (TSC-3)
- ISO-L-EGD (low smoke)
- JASO FC/FD

### Benefits

- Outstanding wear protection
- Virtually residue-free combustion
- 'Low smoke' formulation
- Reduced deposits on piston rings, outlet ports and spark plugs
- Multi-functional application possibilities
- Suitable for air-cooled and water-cooled 2-stroke engines
- Suitable for both separate and mixed lubrication

### Mixing Table

| mixing ratio | 2-stroke oil | Fuel |
|---|---|---|
| 1:50 | 20 ml | 1 l |
| 1:33 | 30 ml | 1 l |
| 1:25 | 40 ml | 1 l |
| 1:20 | 50 ml | 1 l |
| 1:50 | 100 ml | 5 l |
| 1:33 | 150 ml | 5 l |
| 1:25 | 200 ml | 5 l |
| 1:20 | 250 ml | 5 l |

### Typical characteristics

| Property | Method | Unit | Value |
|---|---|---|---|
| Density at 15 °C | ASTM D-7042 | g/ml | 0.864 |
| Color | visuell | - | amber |
| Kinematic viscosity KV 40 | ASTM D-7042 | $mm^2/s$ | 57,5 |
| Flash point | ASTM D-92 / DIN EN ISO 2592 | °C | 132 |
| Pour point | ASTM D-97 / DIN EN ISO 3016 | °C | -32 |

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe-oil.com).

ROWE MINERALÖLWERK GMBH
Langgewann 101, D-67547 Worms



Are you looking for the correct oil for your vehicle?
Scan this code for the ROWE-oilfinder.