

HIGHTEC ATF 9007

High-performance ATF with reduced viscosity for improved fuel economy.

Description

HIGHTEC ATF 9007 is a high-performance, reduced-viscosity ATF based on the latest additives and a special base oil composition of cutting-edge HC-synthesis oils. It was specifically developed for use in the modern 9-speed automatic transmissions found in SUVs, medium-sized and luxury vehicles, for example. The lowered viscosity and optimized viscosity-temperature behaviour enable a marked reduction in the consumption and CO2 emissions.

Application

HIGHTEC ATF 9007 is adapted to the special requirements of modern 9-speed automatic transmissions such as the Mercedes-Benz 9G-TRONIC, where it is used in keeping with the manufacturer's instructions and will even ensure non-slip transmission at very high motor torques with its specific friction coefficient level, thus enabling spontaneous and racy gear changes without sacrificing comfort. The excellent constancy of the friction coefficient guarantees consistent gear shifting performance throughout the entire change interval.

The quality of this product is equivalent to EU regulations

- JASO 1A-LV

Additionally this product is recommended when the following filling instructions are required

- DSIH 6p805
- Hyundai/Kia SPH-IV/SP-IV RR
- Hyundai NWS-9638
- MB 236.16/236.17
- Mitsubishi J3/PA/SP-IV
- Nissan Matic W
- Saab 93 165 147
- Volvo 6 speed MY 2011-2013 (P/N 31256774 or 31256675)
- VW G 055 162/G 052 540

Benefits

- lowered viscosity for best fuel economy (maximum fuel efficiency)
- outstanding constancy of the friction coefficient throughout the entire change interval, ensuring maximum driving and gear shifting comfort
- best wear protection characteristics for reliable function and longest lifetime
- excellent shifting characteristics at low temperatures
- outstanding ageing and oxidation stability
- minimized foaming tendency
- neutral with sealing materials
- blendable and compatible with other ATFs of the same specification. A full oil change is urgently recommended, however, to enjoy all the advantages offered by HIGHTEC ATF 9007.

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.845
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	30,0
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	6,2
Viscosity index	ASTM D-7042	-	163
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	205
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-39

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe-oil.com).

ROWE MINERALÖLWERK GMBH
Langgewann 101, D-67547 Worms



Are you looking for the correct oil for your vehicle?
Scan this code for the ROWE-oilfinder.