

## HIGHTEC BIO SKM

Readily biodegradable saw chain oil.

### Description

HIGHTEC BIO SKM saw chain oil is recommended for lubricating chainsaws from reputable manufacturers.

### Application

HIGHTEC BIO SKM has large power reserves that guarantee less wear and thus a longer service life for the chain, even under adverse operating conditions. The saw chain oil HIGHTEC BIO SKM retains the highest level of wear protection and its slightly thixotropic characteristics due to selected additives.

### Benefits

- Excellent wear protection
- Adherent ('thixotropic')
- Suitable for all applications
- Not water-soluble
- Recommended for use throughout the year due to its optimal viscosity temperature behaviour

### Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.917
Kinematic viscosity KV 40	ASTM D-7042	mm <sup>2</sup> /s	100
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	235
Biodegradability	OECD 301 B	%	>60

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms ([www.rowe-oil.com](http://www.rowe-oil.com)).

