PRODUCT INFORMATION

HIGHTEC Haftöl Spezial ISO VG 680

Special lubricant with adhesive additives and other special additives to provide wear protection for saw frames

Description

HIGHTEC Haftöl Spezial ISO VG 680 is an extremely pressure-resistant and stable special oil for lubricating vertical guideways and slideways. This is highly stringy, wear-reducing and extremely adhesive.
Ideally suitable for use in saw frames. From ISO VG 320, these products contain a very high content of premium Brightstock base oil.
Special mineral oil-based lubricating oil

- With friction and wear-reducing high-pressure additives
- Containing ageing and corrosion protection additives
- Reduction of oil consumption by means of a highly effective adhesive additives

Benefits

- Suitable for all-purpose use
- High level of wear protection
- High adhesiveness
- Good corrosion protection
- Also suitable for non-ferrous metals

Recommendation

For lubricating vertical guideways and slideways

Notices

Used in once-through lubrication, i.e.
if other commonly used lubricants are spun off by vibration, rotation or oscillations.

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.91
Kinematic viscosity KV 40	ASTM D-7042	mm^2/s	680
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	>200

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe-oil.com).

ROWE MINERALÖLWERK GMBH
Langgewann 101, D-67547 Worms

Are you looking for the correct oil for your vehicle?
Scan this code for the ROWE-oilfinder.