

HIGHTEC FORM NPS 45

All-purpose, high-performance, metal forming lubricant with a high level of adhesive strength

Description

HIGHTEC FORM NPS 45 is a non water-miscible, low-viscosity, high-performance oil with a very high additive content. HIGHTEC FORM NPS 45 is suitable for very difficult metal forming processes due to its strongly polar components and its extremely pressure-resistant lubricating film.

Application

HIGHTEC FORM NPS 45 is applied undiluted onto the workpiece by either rolling or spraying.

Benefits

- Heavy-duty forming oil
- Wide field of application
- First-rate pressure absorption capacity
- High EP effect
- Chlorine-free

Recommendation

Field of application:

- Pressing
- Punching
- Drawing, deep drawing
- Fine blanking

HIGHTEC FORM NPS 45 is suitable for machining materials made of steel, stainless steel and aluminium.

Notices

Storage:

When stored in dry, frost-free rooms and in original, unopened containers the storage period is: 36 months
Temperature range: 0-40°C

Degreasing:

HIGHTEC FORM NPS 45 can be degreased with aqueous-alkaline cleaning agents and solvent cleaning agents in the event of planned cleaning of the workpieces.

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.91
Color	visuell	-	brown
VKA welding force	DIN 51 350-4	N	8500
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	45
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	160
Copper corrosion 100 A3	DIN 51759	Ranking	4

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe-oil.com).

